

## Product Datasheet

Part Code: See specifications

# FULL HD 1080P IP camera VR Mini-dome with POE

## Key Features

- 1/2.8 3MP sensor
- Supports H264, H.265
- Supports dual stream.
- Main stream:2304×1296,1920×1080
- Sub-stream: D1(704\*576)/ 360P(640\*360 )/ CIF(352\*288)
- Supports D-WDR, 3D-NR, BLC, Auto-White balance for different environments
- Supports ONVIF
- Supports image shutter, 4 Shutter areas
- Supports audio input
- Supports motion detection
- Supports OSD setting and network programming via browser UI
- Supports mobile surveillance via VMS
- Supports stepless IR and white light mode



## Specifications

Camera	Main Chipset	Hisilicon 3516EV200
	Image Sensor	3MP 1/2.8" sensor (407)
Function	D/N	Support D/N switching (IR-CUT optional)
	Shutter	1/25-1/10000
	White balance	Support auto white balance
	BLC	Support
	Noise Reduction	Support 3D NR
	WDR	Support D-WDR
	Motion Detection	Support
	Privacy shelter	Support 4 areas
	Mirror	Support
	OSD	Support OSD setting
Video	Restart	Support remote restarts via software UI
	Compression	H.264, H.265
	Resolution	Main stream: 2304×1296,1920×1080 Sub stream: 704*576 ,640*360 , 352*288
	Frame rate	3MP(20fps 50HZ/60HZ), 2MP(25fps 50HZ/60HZ)
	Video adjustments	Brightness, saturability, chroma, contrast, sharpness adjustment

## FULL HD 1080P IP camera VR Mini-dome with POE

### Specifications...continued

Network	Ethernet	RJ-45 10M/100M
	Network protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Search(Support P6S IP camera, DVR, NVS and etc.)
	Access protocol	Support ONVIF/private protocol/CGI
Audio	Supported client UI's	iPhone, iPad, Android & Windows
	Audio	G.711U
	Input	1CH In
General Specifications	Output	1CH Out
	Dimensions	H: 46mm x W: 93mm x D: 95mm
	Temperature	-20°C ~ +65°C
	Power	DC12V 2A
Certifications	Humidity	10 ~ 95%
	Ip rating	IP66, IEC 60529
	EMC and electrical safety	CE, E-Mark, EN50155
	Mechanicalimpacts (VR)	IEC 60068-2-75h, IK10 (1.4 50 joules)

### Product Codes

VMD-IPC-2.8-IR-POE	2.8mm Lens
VMD-IPC-3.6-IR-POE	3.6mm Lens
VMD-IPC-6-IR-POE	6mm Lens